



Specification For LED Panel light

PRODUCT NAME: 300x300 Aufbauleuchte

PART NO: 1472 - 1473

Made By	Checked by
OK	OK

CE



ROHS



Features

- Color warmwhite and naturalwhite.
- Color temperature: K3000 - K4000
- Enclosure material: Die-casting
- Power factor>0.95
- Beam angle: 120 Degree
- Saving energy: 50%
- Long lifespan: 30,000Hrs
- IP code: IP20
- Gross weight: 1100 g
- Working voltage: 100-240Vac/50-60Hz
- LED Source: 2835 SMD LED
- Reflector: milkcolor PMMA
- No UV,no IR
- Standard warranty : 2 years
- Safety standard: RoHS, CE pending
-

Applications

LED panel light can be widely used in the hotel, restaurant, supermarket, school, office, factory, fields or open spaces and the other architecture.



Electrical/Optical Characteristics

NUMBER	ITEM	DESCRIPTION
01	Input Voltage	AC100-240V
02	Operating Voltage	DC18V
03	Power Consumption	24W
04	Power Factor	0.90-0.95
05	LED Type	SMD 2835
06	LED Q'ty	120PCS*0.2W
07	Luminous Flux	1800LM
09	CCT	2800-3200K/4000-4750K
10	Beam Angle	120°
11	CRI	≧ 80 Ra
12	Life Time	≧ 29999H
13	Certifications	CE,ROHS
14	IP Code	IP20
15	luminaires Class	Class III
16	Fixing Ways	on-built
17	Operating Temperature	-20℃to+50℃
18	Storage Temperature	-30℃to+60℃
19	Humidity Operating	10-80%RH
20	Humidity Storage	10-90%RH