DUO LED

LED HighBay Light

UFO03 70W-240W

190LM/W

SPECIFICATIONS



5 Years Warranty


CLASSIFIED c UL us SAA APPROVALS CE RoHS LM-79 LM-80


Specification

Luminous Efficiency: 190lm/w ±5%
Input Voltage: AC100-277V 50/60Hz
Power: 70W 90W 110W 150W 200W 240W
Color temperature: 4000K 5000K 5700K
Color Rendering Index: Ra>70
Lifespan: >50,000hours
On-off times:>100,000 Times


Power Factor: >0.95
Beam Angle: 60° 90° 120°
Working Temperature: -30~50℃
Storage Temp: -40~80℃
Environment Humidity: < 95%LED
Type: BRIDGELUX SMD2835
Driver : Meanwell


Case







Specification





60-120W





150-240W


StructurePerformance

Dimensions L x h x W (mm)	ϕ 289*138mm/ ϕ 325*149mm
Housing: material_color	Aluminum，bracket by Carbon Steel (RAL 9017)
Cover: material color	Transparent PC
Cable length mm	500mm
Protection class (IP)	IP65
IK rate	IK08

Product Model

Model No.	Power	CRI	EFF(lm/W)	Lumen(lm)	Size(mm)	Carton Size(mm)	G.W/1PCS
SL-UFOA00-70Y-XXXX-C	70W	Ra70	190	13300	φ289xH176	L320xW320xH185	3.2KG
		Ra80	175	12250			
SL-UFOA00-90Y-XXXX-C	90W	Ra70	190	17100	φ289xH176	L320xW320xH185	3.2KG
		Ra80	175	15750			
SL-UFOA00-110Y-XXXX-C	110W	Ra70	190	20900	φ289xH176	L320xW320xH185	3.2KG
		Ra80	175	19250			
SL-UFOA00-150Y-XXXX-C	150W	Ra70	190	28500	φ325xH187	L380xW380xH185	4.5KG
		Ra80	175	26250			
SL-UFOA00-200Y-XXXX-C	200W	Ra70	190	38000	φ325xH187	L380xW380xH185	4.5KG
		Ra80	175	35000			
SL-UFOA00-240Y-XXXX-C	240W	Ra70	180	43200	φ325xH187	L380xW380xH185	4.5KG
		Ra80	170	40800			

Structure drawing



Environmental Applicability

Storage Temperature/Humidity	-40℃～60℃ / 10%～98%RH
Working Temperature/Humidity	-30℃～50℃ / 20%～95%RH
Ta Max.	ta:50℃
Corrosion Protection	Metal parts shall have the corrosion prevention measures. ■spray powder protection □Coating protection □Stainless steel protection
UV Protection	□Class I Ultraviolet aging for 24 hours □Class II Ultraviolet aging for 72hours ■Class III Ultraviolet aging for 168 hours